

## BASE OIL SN 350 Group A+

No	Test Item	Text Method	Unit	Result
1	Kinematic Viscosity@100°C	ASTM D445	cSt	8.415
2	Kinematic Viscosity@40°C	ASTM D445	cSt	66.55
3	Flash Point	ASTM D92	°C	254
4	Color	ASTM D1500	-	L 0.5
5	Viscosity Index	ASTM D2270	-	95
6	Density@15°C	ASTM D1298	g/cm <sup>3</sup>	0.8785
7	Pour Point	ASTM D97	°C	-12

- \* Better Thermal stability
- \* Better Oxidation stability
- \* Longer service life
- \* Increased component protection
- \* Better resistance to the formation of Laquers and Sludge

**NOTES:**

PORT OF LOADING: JEBEL ALI UNITED ARAB EMIRATES

PACKING: FELEXI BAGS & DRUMS

MOQ: 100 MT EQUAL TO 5 CONTAINERS

DELIVERY TO SHIPPING LINE: WITHIN APPROXIMATLY 10 TO 15 DAYS MAXIMUM

For more info, please be in contact with

UAE Representative, MR KHALIL KHAN +971505658345 [info@rivalstarsltd.com](mailto:info@rivalstarsltd.com)

INDIA Representative MR SANDEEP GUPTA +9198737910579 & [india@rivalstarsltd.com](mailto:india@rivalstarsltd.com)